

MLI Ultra 12/5500



Product code: 66015500

Heavy Duty, Extreme Performance

The MLI series delivers extreme Lithium Ion performance even under the harshest conditions, such as high charge and discharge currents, wet environments, mechanical shocks or vibrations. This is realized by combining our best Lithium-Iron Phosphate (LiFePO4) cells with a proprietary Battery Management System (BMS) inside a sturdy, waterproof housing.

The sophisticated Mastervolt BMS ensures optimal use of each individual cell. Integrated battery monitoring provides you with accurate and up-to-date information on the state of your battery. Integrated NMEA 2000, CZone* or MasterBus communication allows complete system integration, to ensure the best possible recharging, while maximizing the lifetime of your battery.

* Expected December 2019.

Features

- Extreme performance, heavy duty Lithium Ion batteries.
- BMS and LiFePO4 chemistry according to highest safety standards.
- Saves up to 70 % in space and weight.
- More than three times the life span of traditional batteries.
- Fast charging within 60 minutes.
- High charge / discharge rate up to 2.5 C.
- Integrated battery monitoring (Ah consumed, state of charge).
- Series connection up to 10 batteries possible.
- MasterBus communication with any Mastervolt battery charger.
- CZone and NMEA 2000 compatible (expected December 2019).
- Waterproof electronics compartment.
- Designed according to UN38.3.
- CE, E-Mark and DNV-GL (pending).

CAUTION!

For additional safety, Mastervolt stipulates the use of a safety relay as mandatory part of the battery installation.

- safety relay 12 volt, product code [7700B-BSS](#)7700B-BSS

Specifications

General specifications

Nominal battery voltage	13.2 V
Nominal battery capacity	400 Ah
Nominal battery energy capacity	5500
Cycle life	
Max. charge current	500 A (1.25 C)
Continuous charge current	200 A (1 C)
Continuous discharge current	500 A (1.25 C)
Peak discharge current	2000 A (5 C) for 10 s
Battery monitoring	integrated
MasterBus communication	yes
CZone / NMEA 2000 communication	yes, pending (December 2019)
Battery terminals	M8
Mounting position	upright or either long side
Max. outer dimensions (incl. terminals/grip handles), lxwxh	622 x 197 x 355 mm 24.5 x 7.8 x 14.0 inch
Product weight	57 kg 125.7 lb
Shipping weight	60 kg 132.3 lb
Approvals	CE, E-Mark and DNV-GL (pending)

Technical specifications

Battery chemistry	Lithium Iron Phosphate
Protection degree	IP65 (electronics cabinet)
Parallel connection	yes, unlimited
Series connection	yes, up to 10 batteries - systems over 48 V require a separate battery box to prevent access to high voltage parts
Protections	over voltage, under voltage, over temperature
Safety relay	to be added mandatorily, product code 7700B-BSS
Safety relay controls	integrated